

# **SIDE DUMP SEMI TRAILER MODELS, STANDARD FEATURES, AVAILABLE OPTIONS AND SPECIFICATIONS**

## **SINGLE AXLE**

- Custom built to order

## **TANDEM AXLE**

- Standard (39'8" frame, Spring or Air Ride Suspension)

## **TRI AXLE**

- Standard (42'6" frame, Spring or Air Ride Suspension, 100" axle spread)
- Tri Axle Spread (42'6" frame, Air Ride Suspension, 120" axle spread)
- Super-Tri (47' frame, Air Ride Suspension, Tag Axle, 86" axle spread)

## **QUAD AXLE**

- 48' frame, Air Ride Suspension

## **CONVERTOR DOLLIES – TANDEM AND TRIPLE AXLE**

- Hutch CH9700 Cast Spring Suspension
- Multiple tongue lengths
- Holland fixed 5th wheel
- Rubber Bushing Drawbar Eye
- Premier Hinges
- ABS installed
- Full plumbing, wiring and air for operation of 2nd side dump trailer
- Available with Air Ride Suspension

## STANDARD FEATURES

- 50° dump angle
- 35' tub made from Grade 100 steel
- 35' tub built with center pivot point
- Push block with under ride protection bumper
- Bolt on steel front fenders and poly rounded rear fenders
- 5 ½" hydraulic cylinders
- Two-way hydraulics (required on tractor)
- Tarp ready tub
- Parker 60 Series Quick Couplers
- ½" hydraulic hoses
- Hutch CH9700 Cast Spring Suspension
- 25,000 lb. uni-mount axles
- 11R22.5 tires on white steel hub piloted wheels
- 2-speed landing gear
- Synthetic grease-sealed hubs
- LED lights

## AVAILABLE OPTIONS

- Air Ride Suspension
- Lift axle
- Dump directional control valve mounted on trailer
- Custom colors and decaling
- High Side kit (24"-36")
- Air Weigh on board scale
- Electric roll tarp system
- Aluminum wheels
- Super single tire/wheels
- Pintle Package
- Hydraulic Selector Valve